



technology | environment | partnership

# TD702 and TD702C



## Diesel

Trailer or van mounted

### Specification TD702 & TD702C

Pressure:	70-700bar / 987-9877psi*
Flow:	23l / min 1380l / h*
Pump:	Prattisoli industrial pump
Max Temp:	99°C, Cold**
Engine model:	Kubota V2203
Engine power:	37kw / 50hp
Fuel/cylinders:	Diesel / 4 cylinder
Fuel tank:	120litres
Water tank:	1000litres
Trailer dimensions:	399x176x192cm
Van mount dimensions:	200x157x145cm
Weight TD/SD:	1450 / 1150kg

\* infinitely variable pressure and volume  
 \*\* higher temperature can be achieved at reduced flow

### Standard Features/Equipment

Heat exchanger/water cooled diesel engine
Spray gun and lance
50 meters water supply hose on reel
50 meters high pressure hose on reel
Supplied with dump gun with open bypass

### Safety Features

Automatic engine cut out on:
• Open engine lid compartment
• Low water/high temperature in water tank
• Closed chimney lid
• Oil pressure
• Engine overheat protection
Flame surveillance (for automatic safety cut out)
Current temperature display

### Ideal Applications

- Industrial cleaning
- Concrete repair/preparation
- Paint stripping

### Optional Equipment

Automatic throttle control	150°C thermostat
Descale system	Hazard lights
Anti freeze system	Remote control
Electric hose reels	Chemical injection system

### Accessories

Turbo nozzles
Water sand blasting kit
Abrasive cleaning kit
Extension hose and reels
Tank cleaning head
Spray guns and lances



Mandal Alle 3, DK 5500 Middelfart, Denmark T: 0045 64 41 5555 • F: 0045 64 41 7555 • E: info@aquila.dk